

HÜPER OPTIK™



CERAMIC 50

C50

SPECIFICATIONS

	Single Pane	Double Pane
Visible Light Transmission	50%	48%
Visible Light Reflectance	10%	11%
Shading Coefficient	0.58	0.65
Solar Heat Gain Coefficient	0.50	0.56
Infrared Rejection	68%	68%
UV Light Rejection	99%	99%
Total Solar Energy Rejected	50%	44%
Glare Reduction	45%	47%
U-value	1.02	0.46



HUPEROPTIKUSA.COM

HÜPER OPTIK™

FEATURES

- World's first patented nano-ceramic technology
- Superb durability - resistance to seashore (high-salt) environment
- High total solar energy rejection
- Reduces demetallization or discoloration
- High ultraviolet rejection - greater than 99%
- 100% dye-free and 100% metal-free
- Natural tone with low reflectivity
- Scratch-resistant hardcoat

BENEFITS:

- Residential limited lifetime & commercial fifteen-year limited product warranty
- Cutting-edge technology with remarkable heat rejection performance
- Increases comfort - cooler interior
- Reduces glare and fading of interior upholstery
- Saves energy by reducing electricity consumption
- Protects against sun-related skin problems - SPF>200
- Enhances safety with improved glass shatter resistance
- Enhances overall aesthetics with a soft natural tone

FHSPE-C50



Powered by
**Meister
Keramische
Technologie**

